



## TEL15 Headphones



- Low impedance technology
- Integrated clip on front panel
- The headband is made of soft TPE material

### Specifications

Mechanical	
Color	Black
Size (mm)	65 (w) × 10 (h) × 110 (d)
Size packed (mm)	190 (w) × 65 (h) × 215 (d)
Weight (g)	100
Weight with cable (g)	110
Weight packed (g)	200
Cable length (mm)	1500
Cable diameter (mm)	∅ 2.5
Jack	∅ 3.5 mm stereo, right-angled
Ear caps diameter	∅ 53 mm
Ear caps adjustment (via gimbal joint)	± 10° in each direction
Ear pads contact pressure	2.2 N
Adjustment range for head size	63 mm per side
Electrical	
Acoustic	40 mm speaker
Impedance	32 Ω
Sensitivity	98 ±3 dB SPL/V (@ 32 Ω)
THD @ nominal level	< 1% (@ 1 kHz @ 1 mW)
Frequency Range	20-20,000 Hz

### Description

After decades of experience in the field of conferencing, the TEL15 is the apex of Televic's expertise in headphones. A sleek design paired with secure, high-quality audio, creates the perfect pair of headphones. The TEL15's optimal adjustment and lightweight design allows hours of use. After the conference, a simple hygienic tissue will prepare the unit for the next user, without the need to exchange expensive foam cushions. It's flexible enough to achieve different wearing positions. Finally, the cable is very soft and TPU covered to reduce the structure-borne noise.

### Features

- Wide frequency range
- Ultra lightweight
- Wide adjustment range

All information copyright **Televic Conference**, 2015. Version 1.0, October 2015

—  
Leo Bekaertlaan 1 · 8870 Izegem · Belgium

Tel. +32 51 30 30 45

Fax +32 51 31 06 70

E-mail: [conference@televic.com](mailto:conference@televic.com)

Web: <http://www.televic-conference.com>

*Televic reserves the right to change this document without notice.*